

Serial No. 09/660,370

- 2 -

Art Unit: 2134

In the claims:

## 1. (original) A communication system comprising:

a rendezvous point device that forwards multicast communication messages to members of a shared tree;

a designated device in communication with the rendezvous point device via a number of intermediate devices; and

a host device in communication with the designated device, wherein:

the host device sends a join request to the designated device using a predetermined multicast group management protocol in order to join the shared tree for receiving the multicast communication messages forwarded by the rendezvous point device;

the designated device receives the join request and forwards to the rendezvous point device via the number of intermediate devices an encoded join request generated using an authentication key associated with the host device;

the rendezvous point device receives the encoded join request and authenticates the encoded join message using the authentication key associated with the host device; and

the host device is prevented from receiving the multicast communication messages forwarded by the rendezvous point device, if the rendezvous point device determines that the encoded join message is not authentic.

2. (original) The communication system of claim 1, further comprising a key server for authenticating the host device and generating the authentication key for the host device.

3. (original) The communication system of claim 2, wherein the key server provides the authentication key to both the host device and the rendezvous point device using a secure key distribution mechanism.

4. (original) The communication system of claim 1, wherein the host device sends the authentication key to the designated device.

Serial No. 09/660,370

- 3 -

Art Unit: 2134

5. (original) The communication system of claim 4, wherein the host device sends the authentication key to the designated device in the join request.
6. (original) The communication system of claim 5, wherein the predetermined multicast group management protocol is an extended Internet Group Management Protocol (IGMP) including means for including the authentication key in the join request.
7. (original) The communication system of claim 1, wherein the designated device joins the shared tree on behalf of the host device.
8. (original) The communication system of claim 7, wherein the designated device establishes appropriate multicast routes for forwarding multicast communication messages to the host.
9. (original) The communication system of claim 1, wherein each intermediate device receives the encoded join request and forwards the encoded join request toward the rendezvous point device.
10. (original) The communication system of claim 9, wherein each intermediate device that is not already joined to the shared tree joins the shared tree on behalf of the host device and establishes appropriate multicast routes for forwarding multicast communication messages toward the host device upon receiving the encoded join request.
11. (original) The communication system of claim 9, wherein each intermediate device that is already joined to the shared tree waits for an explicit acknowledgment message from the rendezvous point device and establishes appropriate multicast routes for forwarding multicast communication messages toward the host device only upon receiving the explicit acknowledgment message from the rendezvous point device.

Serial No. 09/660,370

- 4 -

Art Unit: 2134

12. (original) The communication system of claim 1, wherein the rendezvous point device sends an explicit acknowledgment message toward the host device upon determining that the encoded join request is authentic.

13. (canceled).

14. (canceled)

15. (canceled)

16. (canceled).

17. (canceled)

18. (currently amended) A method comprising:

obtaining an authentication key; and

sending a join request to a designated device using a predetermined multicast group management protocol, the join request including the authentication key to enable the designated device to encode the join message for authentication by a rendezvous point

19. (original) The method of claim 18, wherein the predetermined multicast group management protocol is an extended Internet Group Management Protocol (IGMP) including means for including the authentication key in the join request.

20. (currently amended) An apparatus comprising:

receiving logic operably coupled to receive an authentication key; and

joining logic operably coupled to send a join request to a designated device using a predetermined multicast group management protocol, the join request including the authentication key to enable the designated device to encode the join message for authentication by a rendezvous point.

Serial No. 09/660,370

- 5 -

Art Unit: 2134

21. (original) The apparatus of claim 20, wherein the predetermined multicast group management protocol is an extended Internet Group Management Protocol (IGMP) including means for including the authentication key in the join request.

22. (currently amended) A computer readable medium having embodied therein a computer program for  
controlling a computer system, the computer program comprising:  
receiving logic programmed to receive an authentication key; and group management logic  
programmed to send a join request to a designated device  
using a predetermined multicast group management protocol, the join request including  
the authentication key to enable the designated device to encode the join message for  
authentication by a rendezvous point.

23. (original) The computer readable medium of claim 22, wherein the predetermined multicast group management protocol is an extended Internet Group Management Protocol (IGMP) including means for including the authentication key in the join request.

24. (original) The computer readable medium of claim 22, wherein the computer readable medium is a computer storage medium.

25. (original) The computer readable medium of claim 22, wherein the computer readable medium is a computer communication medium.

26. (original) A method comprising:  
receiving a join request from a host device;  
generating an encoded join request using an authentication key associated with the host device; and  
sending the encoded join request toward a rendezvous point device.

Serial No. 09/660,370

- 6 -

Art Unit: 2134

27. (original) The method of claim 26, wherein the join request includes the authentication key.

28. (original) The method of claim 26, further comprising:

joining a shared tree on behalf of the host device and establishing appropriate multicast routes for forwarding multicast communication messages to the host device.

29. (original) An apparatus comprising:

receiving logic operably coupled to receive a join request from a host device;  
encoding logic operably coupled to generate an encoded join request using an authentication key associated with the host device; and  
sending logic operably coupled to send the encoded join request toward a rendezvous point device.

30. (original) The apparatus of claim 29, wherein the join request includes the authentication key.

31. (original) The apparatus of claim 29, further comprising:

joining logic operably coupled to join a shared tree on behalf of the host device;  
and  
routing logic operably coupled to establish appropriate multicast routes for forwarding multicast communication messages to the host device.

32. (original) A computer readable medium having embodied therein a computer program for controlling a computer system, the computer program comprising:

receiving logic programmed to receive a join request from a host device;  
encoding logic programmed to generate an encoded join request using an authentication key associated with the host device; and  
sending logic programmed to send the encoded join request toward a rendezvous point device.

Serial No. 09/660,370

- 7 -

Art Unit: 2134

33. (original) The computer readable medium of claim 32, wherein the join request includes the authentication key.

34. (original) The computer readable medium of claim 32, further comprising:  
joining logic operably coupled to join a shared tree on behalf of the host device;  
and  
routing logic operably coupled to establish appropriate multicast routes for forwarding multicast communication messages to the host device.

35. (original) The computer readable medium of claim 32, wherein the computer readable medium is a computer storage medium.

36. (original) The computer readable medium of claim 32, wherein the computer readable medium is a computer communication medium.

37. (canceled)

38. (canceled)

39. (canceled)

40. (canceled)

41. (canceled)

42. (canceled)

43. (canceled)

44. (canceled)

Serial No. 09/660,370

- 8 -

Art Unit: 2134

45. (canceled).

46. (canceled).

47. (canceled).

48. (currently amended) A method comprising:

receiving from a designated routing device coupled to a host, an encoded join request for a the host device, the encoded join request being encoded by the designated routing device using an authentication key associated with the host;

authenticating the encoded join request to determine whether or not the encoded join request is authentic; and

establishing appropriate multicast routes for forwarding multicast communication messages to the host device if and only if the encoded join request is determined to be authentic.

49. (original) The method of claim 48, wherein authenticating the encoded join request comprises:

maintaining a number of authentication keys;

determining the host device for the encoded join request; and searching for an authentication key associated with the host device.

50. (original) The method of claim 49, wherein authenticating the encoded join request further comprises:

failing to find an authentication key associated with the host device; and

determining that the encoded join request is not authentic.

51. (original) The method of claim 49, wherein authenticating the encoded join request further comprises:

Serial No. 09/660,370

- 9 -

Art Unit: 2134

finding an authentication key associated with the host device; and authenticating the encoded join request using the authentication key associated with the host device.

52. (original) The method of claim 48, further comprising:

sending an explicit acknowledgment toward the host device if and only if the encoded join request is determined to be authentic.

53. (currently amended) An apparatus comprising:

receiving logic operably coupled to receive an encoded join request for a host device, the encoded join request being encoded and forwarded by a designated routing device coupled to the host device using an authentication key associated with the host device;

authenticating logic operably coupled to authenticate the encoded join request to determine whether or not the encoded join request is authentic; and

routing logic operably coupled to establish appropriate multicast routes for forwarding multicast communication messages to the host device if and only if the encoded join request is determined to be authentic.

54. (original) The apparatus of claim 53, wherein the authenticating logic is operably coupled to maintain a number of authentication keys, determine the host device for the encoded join request, and search for an authentication key associated with the host device.

55. (original) The apparatus of claim 54, wherein the authenticating logic is operably coupled to determine that the encoded join request is not authentic if the authenticating logic fails to find an authentication key associated with the host device.

56. (original) The apparatus of claim 54, wherein the authenticating logic is operably coupled to authenticate the encoded join request using an authentication key associated with the host device if the authenticating logic finds the authentication key associated with the host device.



Serial No. 09/660,370

- 10 -

Art Unit: 2134

57. (original) The apparatus of claim 53, further comprising:

acknowledgment logic operably coupled to send an explicit acknowledgment toward the host device if and only if the encoded join request is determined to be authentic.

58. (currently amended) A computer readable medium having embodied therein a computer program for controlling a computer system, the computer program comprising:

receiving logic programmed to receive an encoded join request for a host device receiving logic operably coupled to receive an encoded join request for a host device, the encoded join request being encoded and forwarded by a designated routing device coupled to the host device using an authentication key associated with the host device;

authenticating logic programmed to authenticate the encoded join request to determine whether or not the encoded join request is authentic; and

routing logic programmed to establish appropriate multicast routes for forwarding multicast communication messages to the host device if and only if the encoded join request is determined to be authentic.

59. (original) The computer readable medium of claim 58, wherein the authenticating logic is programmed to maintain a number of authentication keys, determine the host device for the encoded join request, and search for an authentication key associated with the host device.

60. (original) The computer readable medium of claim 59, wherein the authenticating logic is programmed to determine that the encoded join request is not authentic if the authenticating logic fails to find an authentication key associated with the host device.

61. (original) The computer readable medium of claim 59, wherein the authenticating logic is programmed to authenticate the encoded join request using an authentication key associated with the host device if the authenticating logic finds the authentication key associated with the host device.

62. (original) The computer readable medium of claim 58, further comprising:

Serial No. 09/660,370

- 11 -

Art Unit: 2134

acknowledgment logic programmed to send an explicit acknowledgment toward the host device if and only if the encoded join request is determined to be authentic.

63. (original) The computer readable medium of claim 58, wherein the computer readable medium is a computer storage medium.

64. (original) The computer readable medium of claim 58, wherein the computer readable medium is a computer communication medium.

65. (original) In a communication system having a host device, a designated device, and a rendezvous point device, a method comprising:

    sending a join request by the host device to the designated device in order to join a shared tree;

    sending an encoded join request by the designated device to the rendezvous point device;

    authenticating the encoded join request by the rendezvous point device;

    adding the host device to the shared tree, if the encoded join request is authentic;

and

    excluding the host device from the shared tree, if the encoded join request is not authentic.

66. (currently amended) A communication message embodied in a data signal which is forwarded between computer devices in a computer network, the communication message comprising a group key for a multicast group and an authentication key for use in authenticating multicast membership requests by a host device.

67. (canceled)

68. (canceled)

69. (canceled)